

SMART FAMILY

NT935 ETH

ETHERNET MODBUS TCP/IP



Via Leonardo da Vinci, 54/56
20094 Corsico (MI) - Italy
T +39 02 4581861 (3 r.a.) - +39 02 48601011
info@tecsystem.it
tecsystem.it | [bit.ly/3M8DK2x](https://www.youtube.com/watch?v=3M8DK2x)



COMPATIBILE | FLESSIBILE | CERTIFICATA

COMPATIBLE | FLEXIBLE | CERTIFIED



Ethernet Modbus TCP/IP

La NT935 ETH è un innovativo dispositivo elettronico a microcontrollore, appositamente studiato per i trasformatori incapsulati in resina e a secco, dotato di porta ETHernet integrata. Grazie alla connettività ETHernet e al protocollo ModBus TCP/IP, è la centralina ideale per essere inserita nei diversi sistemi di acquisizione remota.



The NT935 ETH is an innovative microcontroller electronic device, specifically designed for resin-encapsulated and dry transformers, equipped with an integrated ETHernet port. Thanks to ETHernet connectivity and the ModBus TCP/IP protocol, it is the ideal control unit to be inserted into various remote acquisition systems.

APPLICAZIONE

Data Center
e Grandi Impianti

APPLICATION

Data Centers
and Big Plants

PRODOTTI SERIE ETH: NT538ETH - T1048ETH - CONVETH - ETH MANAGER



CARATTERISTICHE

- Range di Lettura 0-240°C, opzionale -40 + 200°C
- Ingressi: 4 canali Pt100
- Uscite: 5 relè (Fan1-Fan2-Alarm-Trip-Fault)
- Alimentazione: 85-260 Vca/cc
- Ethernet: RJ45 Modbus TCP/IP

VANTAGGI

- Monitoraggio Remoto e Locale
- Integrazione in sistemi SCADA/BMS
- Manutenzione Predittiva
- Flessibilità di conversione
- Certificata: RINA - UL

FEATURES

- Reading Range 0-240°C, optional -40 + 200°C
- Inputs: 4 Pt100 channels
- Outputs: 5 relays (Fan1-Fan2-Alarm-Trip-Fault)
- Power Supply: 85-260 Vac/dc
- Ethernet: RJ45 Modbus TCP/IP

VANTAGGI

- Remote and Local Monitoring
- Integration into SCADA/BMS systems
- Predictive Maintenance
- Conversion Flexibility
- Certified: RINA - UL

ETH SERIES PRODUCTS: NT538ETH - T1048ETH - CONVETH - ETH MANAGER